

INTERLOCKED SOCKET
16A 2P+E 6h 200-250V 50Hz 60Hz II
2GD 130X260MM_PAR Mantle
terminals With mechanical interlock



ATEX directive 2014/34/EU

Commercial Series	ADVANCE-GRP[GD] Series
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING

Rated current	16A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	50Hz
	60Hz
Terminals	Mantle terminals

Group and categories EX II 2GD

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	GRP Glass Reinforced Polyester
Protection degree	Splash proof
Protection degree IP	IP66
Protection degree IK	7J
Contact material	CuZn (brass)
Cable entry	1xM25
Working temperature	-35°C/+60°C
GLOW WIRE	GW 960°C
Self-extinguishing UL94	V0
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C
Padlock	ø5mm

Flange	130X260MM_PAR
--------	---------------

Technical drawing [PDF]
 Technical drawing [DWG]
 Technical drawing [STP]
 Instruction manual
 Instruction manual

Options	With mechanical interlock
Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.
Catalogue notes	You can request the customised configuration of the cable input for the entire series of the ADVANCE-GRP[GD] socket
Catalogue notes	All versions include Ex cable gland and drilled-hole.