

592.R001-02

DP SWITCH

DP SWITCH 16AX NO+NO 2xM20 II 2GD



EN 60079-31 (2014)
 EN 60079-1 (2014)
 EN 60079-7 (2015)
 EN IEC 60079-7/A1 (2018)
 IEC 60079-1 (2014)
 IEC 60079-0 (2017)
 IEC 60079-7 (2017)
 IEC 60079-31 (2022)
 EN 60669-1 (2018)
 IEC 60669-1 (2017)
 EN IEC 60079-0 (2018)
 EN IEC 60079-31 (2024)
 ATEX directive 2014/34/EU

Commercial Series

ROCKER-EX[GD] Series

Synthetical description

DP SWITCH

Mounting version

SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	16AX
---------------	------

Rated voltage	250V
---------------	------

■ EX CHARACTERISTICS

Group and categories EX	II 2GD
-------------------------	--------

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
------------------	------------------

Protection degree	Splash proof
-------------------	--------------

Protection degree IP	IP66
----------------------	------

Material	THERMOPLASTIC
----------	---------------

Protection degree IK	IK07
----------------------	------

Ambient temperature Ta min	-35 °C
----------------------------	--------

Ambient temperature Ta max	60 °C
----------------------------	-------

GLOW WIRE	GW 960°C
-----------	----------

Cable entry	2xM20
-------------	-------

Cable size	ø10-14mm
------------	----------

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)
[Instruction manual](#)
[Instruction manual](#)

■ OPTIONS & VARIOUS NOTES

Notes	NO+NO
-------	-------

Catalogue notes	Polyamide cable glands.
-----------------	-------------------------

Catalogue notes	Cable glands also available in AISI 316L steel (on request).
-----------------	--

Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.
-----------------	--