

SURFACE MOUNTING BOX
95x95x80mm IP66 GW 960°C
TERMINAL BOX PUSH BUTTON
1NO+1NC GREEN THERMOPLASTIC



ATEX directive 2014/34/EU

Commercial Series	COMPACT-EX[GD] Series
Synthetical description	SURFACE MOUNTING BOX

Rated current (value)	16,00 A
Category of use	AC12
Rated Sizing Voltage (Value)	250 V
Maximum power dissipation	1,660 W

Group and categories EX	II 2GD
Modo protezione gas	Ex db eb IIC T6 Gb
Dust protection	Ex tb IIIC T80°C Db IP66

Protection degree	Splash proof
Protection degree IP	IP66
Material	THERMOPLASTIC
Impact resistance	7J
Equipment	Control station
Function	PUSH BUTTON 1NO+1NC
GLOW WIRE	GW 960°C
Colour	GREEN
Cable entry	1xM20
Cable size	ø10-14mm
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	40 °C

Dimensions 95x95x80mm

Components documentation
Components documentation
Technical drawing
Thermal calculation
Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Components documentation
Instruction manual
Instruction manual
Instruction manual

Catalogue notes	ATEX [ATmosphères EXplosibles]: for applications in potentially explosive atmospheres.
-----------------	--